Product data sheet

Specifications



Overload Relay, Motor Logic, solid state overload relay, NEMA Size 1, 3 pole, 9A to 27A, 600VAC, separate mount

9065SF120

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	1
Phase	3 phase
Mounting Support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	2.7 in (68.3 mm)
Width	3.3 in (82.8 mm)
Depth	3.9 in (99.1 mm)
Product Weight	1.21 lb(US) (0.55 kg)

Ordering and shipping details

Category	US10CP121662
Discount Schedule	0CP1
GTIN	785901749936
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.100 in (12.954 cm)
Package 1 Width	5.200 in (13.208 cm)
Package 1 Length	6.200 in (15.748 cm)
Package weight(Lbs)	16.288 oz (461.757 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	147
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	40.000 in (101.600 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	180.0010 lb(US) (81.647 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**13 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**6 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**5 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.8 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**B65c2eed-aa1c-465f-bca3-a7c8f0610a23**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**42**
Circularity Profile	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Technical Illustration

Dimensions

