Product data sheet

Specifications

Transformer, dry type, encapsulated, 15kVA, 3 phase, 480V primary, 208Y/120V secondary, 14C, 115C rise [TAA]

15T68F

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Dry type transformer

Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
GTIN	785901359517
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	27.00 in (68.58 cm)
Package 1 Width	16.13 in (40.97 cm)
Package 1 Length	20.0 in (50.8 cm)
Package weight(Lbs)	326.00002 lb(US) (147.871 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	40.0 in (101.6 cm)
Package 2 Width	40.0 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	1957.759 lb(US) (888.024 kg)

Compliance

Compliance	TAA Compliant

Contractual warranty

Warranty (in months)	18

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**


Use Again

Repack and remanufacture

Take-back	**No**


Technical Illustration

Dimensions



Technical Illustration

Wiring diagram



15T68F

4 – 2.5%, 2 FCAN AND 2 FCBN

480 DELTA – 208Y/120 CONNECT TO TAPS		
PRIMARY VOLTS	2–5% FCBN	2–2.5% FCAN 2–2.5% FCBN
504	–	H1, H2, H3
492	–	H4, H5, H6
480	H1, H2, H3	H7, H8, H9
468	–	H10, H11, H12
456	H4, H5, H6	H13, H14, H15
432	H7, H8, H9	–