Rittal – The System.

Faster – better – everywhere.

Interface Covers, Modular – SZ 2482.560

Date : May 29, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Interface Covers, Modular – SZ 2482.560

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	For universal use where rapid access to interfaces and outlets is needed. The housing remains closed, protecting it from environmental effects and unauthorized access.
Function principle:	The cover on the mounting frame can be opened at various angles from 90° to 180° The snap fit closure ensures a good seal. The cover can be locked if necessary. All SUB-D interfaces can be turned in the insert
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate
Surface finish:	Mounting frame and metal flap: Matt nickel-plated
Color:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly
Note on Model No.::	Conductively connected to mounting frame.

Product features

Version:	Note: Conductively connected to mounting frame.
Installation options:	as programmer interface for controllers as maintenance access for networks For temporary connection of additional equipment For quick connection to existing network structures for programming and maintenance of integral components

Packaging unit:	1 pc(s).
Weight/packaging unit:	0.06 kg (0.1 lb.)
EAN:	4028177490833
Customs tariff number:	85369095
ETIM 6.0:	EC002625
ETIM 5.0:	EC002608
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	27189234
eCl@ss 6.0/6.1:	27189234
eCl@ss 5.1/5.1.4:	27189238
Product description (long):	SZ Interface flap, modular, interface inserts, 2 x RJ 45, jack/jack, Cat. 5e

Approvals

Approvals:	C-UR UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity