Rittal – The System.

Faster – better – everywhere.

FlatBox – DK 7507.100

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

FlatBox – DK 7507.100

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	with 19" mounting rails
Description:	For flexible use as a wall-mounted or floor-standing enclosure.
Benefits:	Tool-free quick mounting System accessories on the open 19" frame
Material:	Carbon steel Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Color:	RAL 7035
Supply includes:	Flat-packed enclosure 1 wall section 2 basic supports 2 roof/base plates, with cut-outs for cable entry via brush strips 2 side panels, lockable 1 glazed door, lockable, security lock 3524 E, door catch freely selectable Connection components for tool-free, fast assembly Grounding kit for system-compatible grounding of all enclosure parts 19" profile rails
Note:	Max. installation depth: Depth - 58 mm to rear panel Max. distance between two 19" levels: Depth - 104 mm
Base material:	Carbon steel

Â© Rittal 2018

Product features

Dimensions:	Height: 358 mm (14 ″) Width: 600 mm (24 ″) Depth: 600 mm (24 ″)
Installation height for components:	6 U (6 U)
Packaging unit:	1 pc(s).
Weight/packaging unit:	24 kg (52.9 lb.)
EAN:	4028177551435
Customs tariff number:	94032080
ETIM 6.0:	EC002500
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	DK FlatBox, WHD: 600x358x600 mm, 6 U, with 482.6 mm (19") mounting angles