Rittal – The System.

Faster – better – everywhere.

Compact enclosures AE Stainless steel – AE 1012.600

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Compact enclosures AE Stainless steel – AE 1012.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Housing: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Carbon steel Stainless steel 1.4301 (AISI 304) Lock Insert: Die-cast zinc, nickel-plated
Surface finish:	Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
IK code:	IK08
Supply includes:	Housing with door(s) Mounting plate Lock: 3 mm double-bit
Product modification:	Starting in August 2016, the surface grinding is changing from 240 grain to 400 grain. The visually finer grinding pattern will enhance the cleaning properties of the housing.
Base material:	Stainless steel

Product features

Dimensions:	Height: 760 mm (30 ″) Width: 600 mm (24 ″) Depth: 210 mm (8.3 ″)

© Rittal 2018

Mounting plate:	Height: 730 mm (29 ″) Width: 549 mm (22 ″)
Number of doors:	1
Lock version:	Cam
No. of locks:	2
Lock Insert:	3 mm double-bit
Packaging unit:	1 pc(s).
Weight/packaging unit:	30.2 kg (66.6 lb.)
EAN:	4028177000476
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	AE Compact enclosure, WHD: 600x760x210 mm, Stainless steel 1.4301, with mounting plate, single-door, with two cam locks

Approvals

Approvals:	Bureau Veritas CSA DNV-GL Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code Protection category
Declarations:	Declaration of conformity

© Rittal 2018