Rittal – The System.

Faster – better – everywhere.

Fuse Holders 61 A to 400 A – SV 9345.100

Date : May 29, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Fuse Holders 61 A to 400 A – SV 9345.100

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Version:	For busbar systems
Material:	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
Color:	Chassis: RAL 7035 Cover: RAL 7035/7001
Note:	UL (listed accessory) is met through use of the fuse holder on RiLine busbar systems

Product features

Suitable for busbars:	with cross-section height: 5 mm (0.2 ″) with cross-section height: 10 mm (0.39 ″)
Number of poles:	3-pole
For bar systems with center-to-center spacing:	60 mm
Dimensions:	Height: 288 mm (11 ″) Width: 184 mm (7.2 ″)
Type of connection (electrical):	Box terminal
Rated operating voltage:	600 V, 3~

Â© Rittal 2018

Connection for round conductor cross-sections:	AWG 2 – MCM 300
Rated operating current min.:	61 A
Rated operating current max.:	100 A
Cable outlet:	Top/bottom
Suitable for fuses:	Fuse type (class): J Fuse standard: UL 4248-8 Ø x length: 29 mm x 118 mm
Packaging unit:	1 pc(s).
Weight/packaging unit:	2.62 kg (5.8 lb.)
EAN:	4028177615656
Customs tariff number:	85365080
ETIM 6.0:	EC001900
ETIM 5.0:	EC001900
eCl@ss 8.0/8.1:	27400613
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Fuse holder, Class J, 61-100 A, 600 V, 3-pole, (60 mm)

Approvals

Approvals:	C-UR UL + C-UL UR
Certificates:	EAC