Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 Stainless steel – TS 8456.600

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying systems TS 8 Stainless steel – TS 8456.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Base plates: Stainless steel 1.4301 (AISI 304), 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame and base plates: Uncoated Door, roof and rear panel: Exterior brushed, grain size 400 Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Base Plates Rear panel Mounting plate 4 eyebolts Lock: 3 mm double-bit 2 TS punched rails, 18 x 38 mm
Product modification:	Starting March 2017, external fitting and lock components will be manufactured from stainless steel so that they can handle even the harshest operating conditions.
Note:	Due to the hardness of the material, we recommend using metal multi-tooth screws for the

© Rittal 2018

	interior installation.
Base material:	Stainless steel

Product features

Dimensions:	Height: 1800 mm (71 ″) Width: 1200 mm (47 ″) Depth: 400 mm (16 ″)
Mounting plate:	Height: 1696 mm (67 ″) Width: 1099 mm (43 ″)
Number of doors:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	170.4 kg (375.7 lb.)
EAN:	4028177300736
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	TS Bayed enclosure system, WHD: 1200x1800x400 mm, Stainless steel 1.4301, with mounting plate, two doors at the front

Approvals

Approvals:	Bureau Veritas CSA Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code

Declarations:	Declaration of conformity Manufacturer's declaration