Rittal – The System.

Faster – better – everywhere.

Air/Water Heat Exchangers wall-mounted – SK 3212.024

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Air/Water Heat Exchangers wall-mounted – SK 3212.024

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Water-carrying parts copper/brass (Cu/CuZn)
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Wired ready for connection (plug-in terminal strip) Drilling template Sealing and assembly components

Product features

Total cooling output:	L 35 W 10 at 200 l/h: 0.3 kW (1023 BTU)
Air throughput (unimpeded air flow):	Internal circuit with DC: 250 m³/h (147.1 cfm)
Rated operating voltage:	24 V (DC)
Dimensions:	Height: 300 mm (12 ″) Width: 150 mm (5.9 ″) Depth: 85 mm (3.3 ″)
Temperature range:	Operation (environment): +1°C...+70°C Water inlet: +1°C...+30°C
Refrigerant/cooling medium:	Cooling medium: Water (see Internet for specifications)

Â© Rittal 2018

Rated power Pel:	26 W
Duty cycle:	100 %
Rated current (max.):	with DC: 1.2 A
Miniature circuit-breaker/fuse:	2 A
Permissible operating pressure (p. max.):	1 bar - 10 bar
Water connections:	⅜" connector sleeve
Packaging unit:	1 pc(s).
Weight/packaging unit:	3.2 kg (7.1 lb.)
EAN:	4028177430921
Customs tariff number:	84158300
ETIM 6.0:	EC002515
ETIM 5.0:	EC002515
eCl@ss 8.0/8.1:	27180712
eCl@ss 7.0/7.1:	27180712
eCl@ss 6.0/6.1:	27180712
eCl@ss 5.1/5.1.4:	27180712
Product description (long):	SK Air/water heat exchanger, wall-mounted, 0.3 kW, 24 V (DC), Water-carrying parts: copper/brass , WHD: 150 x 300 x 85 mm

Approvals

Approvals:	Approval overview
Certificates:	EAC
Declarations:	Declaration of conformity