Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 Single – TS 8825.500

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying systems TS 8 Single – TS 8825.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
Supply includes:	Enclosure frame with door Roof plate Rear panel, detachable 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting plate

Product features

Dimensions:	Height: 2200 mm (87 ″) Width: 800 mm (31 ″) Depth: 500 mm (20 ″)

Number of doors:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	92.3 kg (203.5 lb.)
EAN:	38080

Approvals

Approvals:	Bureau Veritas CSA DNV-GL Russian Maritime Register of Shipping TÜV UL + C-UL