Rittal – The System.

Faster – better – everywhere.

TopTherm Blue e Wall-Mounted Cooling Units, NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3328.504

Date : May 24, 2018

TopTherm Blue e Wall-Mounted Cooling Units, NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3328.504

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Stainless steel 1.4404 (AISI 316L)
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit IP 55
Protection category NEMA:	NEMA 4X
Supply includes:	Nano-coated condenser Integral electric condensate evaporation Wired ready for connection (plug-in terminal strip) Drilling template Fasteners
Note:	3303.XXX without integral condensate evaporation

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 2.2 kW (7506 BTU) L 35 L 35 at 60 Hz: 2.56 kW (8735 BTU) L 35 L 50 at 50 Hz: 1.62 kW (5527 BTU) L 35 L 50 at 60 Hz: 1.75 kW (5971 BTU)
Air throughput (unimpeded air flow):	External circuit: 980 m³/h (576.8 cfm) Internal circuit: 980 m³/h (576.8 cfm)
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 1650 mm (65 ″)

© Rittal 2018

	Width: 405 mm (16 ″) Depth: 388 mm (15 ″)
Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+50°C Setting range: +20°C...+50°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 900 g (31.7 oz) Global Warming Potential (GWP): 1430 CO_2 equivalent (CO_2e): 1.29 t
Rated power Pel:	L 35 L 35 at 50 Hz: 0.91 kW L 35 L 35 at 60 Hz: 1.03 kW L 35 L 50 at 50 Hz: 1.06 kW L 35 L 50 at 60 Hz: 1.25 kW
Rated current (max.):	At 50 Hz: 6.1 A At 60 Hz: 6.6 A
Start-up current (max.):	At 50 Hz: 20 A At 60 Hz: 22 A
Miniature circuit-breaker/fuse:	16 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.4
Packaging unit:	1 pc(s).
Weight/packaging unit:	80 kg (176.4 lb.)
EAN:	4028177384453
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704

© Rittal 2018

Product description (long):	SK cooling unit Blue e, wall-mounted, NEMA 4X, 2.2 kW, 230 V, 1~, 50/60 Hz, Stainless steel, WHD: 405 x 1650 x 388 mm

Approvals

Approvals:	CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation