Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 Electronic enclosure – TS 8438.510

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying systems TS 8 Electronic enclosure – TS 8438.510

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Front frame: Extruded aluminum sections with die-cast zinc corner pieces Rear door: Carbon steel, 2.0 mm Base plates: Carbon steel, 1.5 mm Adapter sections: Aluminum
Surface finish:	Enclosure frame: Dipcoat-primed Roof and rear door: dipcoat primed, powder-coated on the outside, textured paint Front frame: Powder-coated Base plates: Zinc-plated
Color:	RAL 7035
IK code:	IK09
Supply includes:	Enclosure frame Front frame (r/h hinge, opening angle 130°, held on the left via mechanical snap fasteners) Rear door (r/h hinge, may be swapped to opposite side) Roof plate Adapter section, 482.6 mm (19") mounting level Base Plates 2 support strips fitted in the enclosure depth
Base material:	Carbon steel

Product features

Dimensions:	Height: 2000 mm (79 ″) Width: 600 mm (24 ″)

© Rittal 2018

	Depth: 800 mm (31 ″)
Installation height for components:	42 U (42 U)
Packaging unit:	1 pc(s).
Weight/packaging unit:	75.4 kg (166.2 lb.)
EAN:	4028177236349
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	TS Bayed enclosure system, WHD: 600x2000x800 mm, Sheet steel, with hinged front frame, 482.6 mm (19") mounting angles, single door at the rear

Approvals

Approvals:	UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity Manufacturer's declaration