Rittal – The System.

Faster – better – everywhere.

Interface extension with wall connection – SZ 2482.210

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Interface extension with wall connection – SZ 2482.210

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	USB wall-mounted jack type A on internal connector type A
Description:	To extend the internal housing interfaces, e.g., from industrial PCs and switches to the outside of the enclosure. The wall connection only takes up as much space as a switch.
Benefits:	Rapid access for maintenance work The protection category of the enclosure is preserved The lock nut cuts automatically into the spray-finish, thereby creating a conductive connection. Captive protective cap
Material:	Housing: Brass Cover: Aluminum Seal: Polyamide
Surface finish:	Housing: Nickel-plated Cover: Natural anodized
Protection category IP to IEC 60 529:	IP 66/67 with the protective cap closed

Product features

Dimensions:	Length: 0.5 m (20 ″)
For material thicknesses:	1 mm - 6 mm
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.08 kg (0.2 lb.)

Â© Rittal 2018

EAN:	4028177516311
Customs tariff number:	85369095
ETIM 6.0:	EC001408
ETIM 5.0:	EC001408
eCl@ss 8.0/8.1:	19059205
eCl@ss 7.0/7.1:	27189190
eCl@ss 6.0/6.1:	27189190
eCl@ss 5.1/5.1.4:	27189238
Product description (long):	SZ Interface extension, with wallconnection, USB, L: 500 mm

Approvals

Certificates:	EAC