Product data sheet

Specifications



Transformer, dry type, encapsulated, 15kVA, 3 phase, 480V primary, 240V secondary, 14C, 115C rise [TAA]

15T75F

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Dry Sealed Transformer
Primary to Secondary Voltage	480 V delta 240 V delta
Full Capacity Taps	4 2.5 % FCBN

Complementary

Enclosure Code	14C
Phase	3 phase
Power Rating	15 kVA
Temperature rise	115 °C
Height	14.75 in (374.65 mm)
Width	19.1 in (485.1 mm)
Depth	12.25 in (311.15 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	CSA UL Listed cULus

Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
GTIN	785901358053
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	14.750 in (37.465 cm)
Package 1 Width	19.100 in (48.514 cm)
Package 1 Length	12.250 in (31.115 cm)
Package weight(Lbs)	326.00002 lb(US) (147.871 kg)

Compliance

Compliance	TAA Compliant

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**


Use Again

Repack and remanufacture

Take-back	**No**


Technical Illustration

Dimensions



Technical Illustration

Wiring diagram



9T75F
15T75F
4 – 2.5% FCBN

480 DELTA – 240 DELTA CONNECT TO TAPS	
PRIMARY VOLTS	4–2.5 % FCBN
480	H1, H2, H3
468	H4, H2, H5
456	H6, H2, H7
444	H8, H2, H9
432	H10, H2, H11