Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure for Disconnect – WM 8018.981

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure for Disconnect – WM 8018.981 - WM603816XC

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel.
Material:	Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel, zinc-plated
Surface finish:	Dipcoat-primed and powder-coated, textured paint
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Flange door with universal disconnect cutout 3-point latching L-Handle

Product features

Dimensions:	Height: 1500 mm (59 ″) Width: 975 mm (38 ″)

	Depth: 400 mm (16 ″)
Material thickness::	Housing: 2 mm (0.08 ″) Door: 2 mm (0.08 ″) Mounting plate: 3 mm (0.12 ″)
Mounting plate:	Height: 1455 mm (57 ″) Width: 840 mm (33 ″)
Packaging unit:	1 pc(s).
Weight/packaging unit:	119 kg (262.3 lb.)
EAN:	85758

Approvals

Approvals:	UL + C-UL