Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.587

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.587 - WM426012NC

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Dipcoat-primed and powder-coated, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12 NEMA 12
Supply includes:	Housing with door(s) Mounting plate Rear wall mounting holes

Product features

Dimensions:	Height: 1050 mm (41 ″) Width: 1500 mm (59 ″) Depth: 300 mm (12 ″)
Material thickness::	Housing: 2 mm (0.08 ″) Door: 2 mm (0.08 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 1000 mm (39 ″) Width: 1450 mm (57 ″)

Number of doors:	2
3-point locking system:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	118 kg (260.1 lb.)
EAN:	83164

Approvals

Approvals:	UL