Rittal – The System.

Faster – better – everywhere.

TopTherm air/air heat exchanger wall-mounted with controller – SK 3127.115

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TopTherm air/air heat exchanger wall-mounted with controller – SK 3127.115

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Color:	RAL 7035
Protection category IP to IEC 60 529:	Internal circuit, IP 54
Supply includes:	Complete unit ready for connection Plug-in terminal strip Floating fault signal contact in case of overtemperature

Product features

Specific thermal output:	30 W/K
Air throughput (unimpeded air flow):	External circuit at 50 Hz: 480 m³/h (282.5 cfm) External circuit at 60 Hz: 525 m³/h (309 cfm) Internal circuit at 50 Hz: 480 m³/h (282.5 cfm) Internal circuit at 60 Hz: 525 m³/h (309 cfm)
Rated operating voltage:	115 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 950 mm (37 ″) Width: 400 mm (16 ″) Depth: 205 mm (8.1 ″)
Temperature control:	Electronic Control with Digital Display (factory setting +35°C)
Temperature range:	Operation (environment): -5°C...+55°C

© Rittal 2018

Output per fan:	At 50 Hz: 60 W At 60 Hz: 75 W
Rated current (max.):	per fan at 50 Hz: 0.55 A per fan at 60 Hz: 0.7 A
Miniature circuit-breaker/fuse:	2 A
Packaging unit:	1 pc(s).
Weight/packaging unit:	18 kg
EAN:	4028177425095
Customs tariff number:	84158300
ETIM 6.0:	EC002514
ETIM 5.0:	EC002514
eCl@ss 8.0/8.1:	27180711
eCl@ss 7.0/7.1:	27180711
eCl@ss 6.0/6.1:	27180711
eCl@ss 5.1/5.1.4:	27180711

Approvals

Approvals:	Approval overview UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity