Rittal – The System.

Faster – better – everywhere.

Mounting angles, 482.6 mm (19") for TS, CS Toptec – DK 7827.200

Date : Jun 8, 2018

Mounting angles, 482.6 mm (19") for TS, CS Toptec – DK 7827.200

created: 08.06.2018 on www.rittal.com/ie-en



Product description

Design:	Cranked
Benefits:	Integral U markings in the front facilitate systematic assembly within the 482.6 mm (19˝) attachment level.
Material:	Sheet steel, 2 mm
Technical specifications:	Integral 482.6 mm (19") punchings (EIA standard) Side round and square punchings Clear chromated for conductive connection of the 482.6 mm (19") installed equipment.
Supply includes:	Assembly parts
Note:	The mounting angles can also be used to accommodate 21", 23" and 24" attachment dimensions.

Product features

To fit:	Enclosure type: TS 8 Enclosure type: CS Toptec Height: 2000 mm
Dimensions:	Width: 482.6 mm Width: 19"
Units:	42 U

Packs of:	2 pc(s).
Weight/pack:	6.15 kg
EAN:	4028177234932
Customs tariff number:	73269098
ETIM 6.0:	EC002620
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	27189261
eCl@ss 6.0/6.1:	27189261
eCl@ss 5.1/5.1.4:	27182504