Rittal – The System.

Faster – better – everywhere.

Pivoting frame, large, with trim panel for TS, SE, 800 mm wide enclosures – SR 2346.235

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Pivoting frame, large, with trim panel for TS, SE, 800 mm wide enclosures – SR 2346.235

created: 24.05.2018 build on www.rittal.com/us-en







Product description

Version:	19" level side
Description:	To mount 482.6 mm (19") equipment.
Material:	Carbon steel
Surface finish:	Frame: Zinc-plated Panel: Spray-finished
Color:	RAL 7035
Mounting tip:	Depending on the installation situation TS punched sections with mounting flange, 23 x 73 mm, or TS punched sections with mounting flange, 17 x 73 mm are required
Supply includes:	Locking rod system with double-bit lock insert Material for attaching
Note:	see "Technical Details" for other expansion options In the case of TS and SE two-door enclosures with heights of 1800 mm or 2200 mm, the next smallest pivoting frame must be fitted to prevent a collision with the lock

Product features

Suitable for:	Enclosure type: TS Enclosure type: SE Height: 2200 mm (87 ″) Width: 800 mm (31 ″)

Â© Rittal 2018

Installation options:	In TS/SE with opening angle of 130° or 180°, depending on the selected installation kit
Height units:	45 U
Packaging unit:	1 pc(s).
Weight/packaging unit:	24.9 kg (54.9 lb.)
EAN:	4028177165236
Customs tariff number:	94039010
ETIM 6.0:	EC002620
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	27189261
eCl@ss 6.0/6.1:	27189261
eCl@ss 5.1/5.1.4:	27189239
Product description (long):	SR Swing frame, large, with trim panel, for TS, SE, for W: 800 mm, (45 U), Mounting position side

Approvals

Certificates:	EAC