Rittal – The System.

Faster – better – everywhere.

Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.970

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.970

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:	Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length.
Material:	Flame-resistant plastic to DIN 4102/B1
Color:	RAL 7035
Supply includes:	Flat duct Compensating hose
Note:	Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unit may be reduced, depending on the application in question. For devices 3359..../3382...., the air duct adapter 3286.840 is additionally required.
Suitable for Model No.:	3386.... 3387....

Product features

Packaging unit:	1 pc(s).
Weight/packaging unit:	4.05 kg (8.9 lb.)
EAN:	4028177325456

© Rittal 2018

Customs tariff number:	39269097
ETIM 6.0:	EC001292
ETIM 5.0:	EC001292
eCl@ss 8.0/8.1:	22410601
eCl@ss 7.0/7.1:	27189269
eCl@ss 6.0/6.1:	27189269
eCl@ss 5.1/5.1.4:	27180792
Product description (long):	SK Air duct system, for SK 3209/3210/3273/3359/3382/3383/3384/3385, WHD: 229 x 1500 x 29 mm

© Rittal 2018