Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.534

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.534 - WM241606NC

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

Product features

Dimensions:	Height: 600 mm (24 ″) Width: 400 mm (16 ″) Depth: 150 mm (5.9 ″)
Material thickness::	Housing: 1.5 mm (0.06 ″) Door: 1.5 mm (0.06 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 570 mm (22 ″) Width: 354 mm (14 ″)

Packaging unit:	1 pc(s).
Weight/packaging unit:	16 kg (35.3 lb.)
EAN:	83121

Approvals

Approvals:	UL