Rittal – The System.

Faster – better – everywhere.

Universal light with integral motion detector – SZ 4155.110

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Universal light with integral motion detector – SZ 4155.110

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	Compact 18 W fluorescent tubes with high light output.
Benefits:	Simple, fast mounting
Material:	Plastic
Supply includes:	Universal light Integral motion detector Light (bulb) Light cover Assembly components

Product features

Dimensions:	Height: 95 mm (3.7 ″) Width: 345 mm (14 ″) Depth: 55 mm (2.2 ″)
Rated operating voltage:	110 V - 240 V, 1~, 50 Hz/60 Hz
Installation options:	TS horizontal profile from roof frames: direct TS, SE vertical section: with TS adapter bracket SE sections on front and rear of roof frame: with TS adapter bracket SE profiles to the side of roof frames: direct AE, CM, TP: with universal bracket AE: with rail for interior installation
Operating temperature:	Operation (environment): -15°C...+45°C Storage: -20°C...+70°C

© Rittal 2018

Power consumption:	18 W
Equipment (electrical):	Ballast: Wide range voltage EB Light (bulb): Compact fluorescent lamp, G24q-3 backplate Number of sockets: 1 Jack/outlet (type): D, ground pin (type F, CEE 7/3) Integral motion detector: yes Switch (type): Integral, on/off/motion detector mode
Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply through connector Through-wiring (configuration of row of luminaires)
Light – installation type:	Screw fastening
Light cover:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.92 kg (2 lb.)
EAN:	4028177679832
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Universal light, WHD: 343x95x55 mm, 18 W, 110-240 V, 50/60 Hz, with integral motion detector, with earthing-pin socket, VDE

Approvals

Certificates:	EAC
Declarations:	Declaration of conformity