Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.558

Date : May 25, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.558 - WM423008NC

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes 3-point latching L-Handle

Product features

Dimensions:	Height: 1050 mm (41 ″) Width: 760 mm (30 ″) Depth: 210 mm (8.3 ″)
Material thickness::	Housing: 2 mm (0.08 ″) Door: 2 mm (0.08 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 704 mm (28 ″) Width: 1020 mm (40 ″)

© Rittal 2018

Packaging unit:	1 pc(s).
Weight/packaging unit:	63 kg (138.9 lb.)
EAN:	83137

Approvals

Approvals:	UL

© Rittal 2018