Rittal – The System.

Faster – better – everywhere.

Enclosure Light – SZ 9968.111

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Enclosure Light – SZ 9968.111

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Benefits:	Designed for quick and easy installation External terminal block allows no need to disassemble the light to make electrical connections Available in 15 or 18 watt rating, they can be used with or without the Rittal door switch. Equipped with interference suppression capacitor or a RFI filter, they also come with or without a lamp shade or 115 V U.S. style receptable.
Material:	Lamp holder: polycarbonate Switch: polyester and polycarbonate Terminal block: nylon
Color:	RAL 7044
Supply includes:	Fasteners

Product features

Dimensions:	Height: 110 mm (4.3 ″) Width: 467 mm (18 ″) Depth: 45 mm (1.8 ″)
Rated operating voltage:	120 V, 60 Hz
Equipment (electrical):	Light (bulb): Cool white flourescent Switch (type): On/off rocker switch
Luminous flux:	1170 lm
Connection options:	L1, N, GND

Â© Rittal 2018

Light – installation type:	Screw fastening
Light – mounting option:	TS vertical profile, direct TS roof frame (horizontal profile), direct
Packaging unit:	1 pc(s).
Weight/packaging unit:	1.8 kg (4 lb.)
EAN:	19130