Rittal – The System.

Faster – better – everywhere.

TS punched rail, 25 x 38 mm – TS 8612.760

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TS punched rail, 25 x 38 mm – TS 8612.760

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:	For heavy installed equipment, with mounting holes.
Material:	Carbon steel, 3.0 mm
Surface finish:	Zinc-plated
Supply includes:	Assembly screws
Note:	In conjunction with the snap-on nut, particularly well-suited for dynamic connections

Product features

Suitable for:	Width/depth: 600 mm
Installation options:	On the vertical TS, SE enclosure section With 9 mm round holes all round on a 25 mm hole pattern For the external mounting of support rails, system support rails, C rails 30/15, cable clamp rails (angle section) and own assemblies
Packaging unit:	2 pc(s).
Weight/packaging unit:	2.05 kg (4.5 lb.)
EAN:	4028177429147
Customs tariff number:	73269098

ETIM 6.0:	EC002620
ETIM 5.0:	EC002518
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	23159101
eCl@ss 6.0/6.1:	23159101
eCl@ss 5.1/5.1.4:	27189232
Product description (long):	TS Punched rail 25 x 38 mm, for WD: 600 mm

Approvals

Certificates:	EAC