Rittal – The System.

Faster – better – everywhere.

Compact enclosures AE – AE 1030.500

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Compact enclosures AE – AE 1030.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
IK code:	IK08
Supply includes:	Housing with hinged door(s), of all-round solid construction Flange (gland) plate(s) in enclosure base Mounting plate Lock: 3 mm double-bit
Base material:	Carbon steel

Product features

Dimensions:	Height: 300 mm (12 ″) Width: 380 mm (15 ″) Depth: 155 mm (6.1 ″)
Material thickness::	Housing: 1.38 mm (0.05 ″) Door: 1.5 mm (0.06 ″)

	Mounting plate: 2 mm (0.08 ″)
Mounting plate:	Height: 275 mm (11 ″) Width: 334 mm (13 ″)
Number of doors:	1
Door catch on right, may be swapped to the left:	yes
Lock version:	Cam
No. of locks:	1
Lock Insert:	3 mm double-bit
Flange plate, size:	3
Flange plate, qty:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	7.4 kg
EAN:	4028177251960
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	AE Compact enclosure, WHD: 380x300x155 mm, Sheet steel, with mounting plate, single-door, with one cam lock

Approvals

Approvals:	Bureau Veritas CSA DNV-GL

	Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code Protection category
Declarations:	Declaration of conformity