Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 – TS 8485.510

Date : May 29, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying systems TS 8 – TS 8485.510

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55 in conjunction with side panels and gland plates
Protection category NEMA:	NEMA 12 in conjunction with side panels and gland plates
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit
Note on Model No.::	without tubular door frame, mounting plate, slide rail or base plates
Base material:	Carbon steel

Product features

© Rittal 2018

Dimensions:	Height: 1800 mm (71 ″) Width: 400 mm (16 ″) Depth: 500 mm (20 ″)
Number of doors:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	49.2 kg (108.5 lb.)
EAN:	4028177357242
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	TS Bayed enclosure system, WHD: 400x1800x500 mm, Sheet steel, without mounting plate, single door at the front

Approvals

Approvals:	Bureau Veritas CSA DNV-GL Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code
Declarations:	Declaration of conformity Manufacturer's declaration