Rittal – The System.

Faster – better – everywhere.

TS IT Network/Server Enclosure With vented door for room climate control, North American version – DK 5508.210

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TS IT Network/Server Enclosure With vented door for room climate control, North American version – DK 5508.210

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Carbon steel Aluminum
Surface finish:	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder coated
General color:	RAL 7035
Color:	Enclosure frame and panels: RAL 9005 Interior installation: RAL 9005
Supply includes:	Enclosure frame TS 8 with doors and roof plate Aluminum sheet steel door at the front, vented (vented surface area approx. 85% perforated), 180° hinges Carbon steel door at the rear, vertically divided, vented (vented surface area approx. 85% perforated), 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Roof plate, multi-piece, removable, with side cable entry in the depth and covered cut-out for fan mounting plate Spacers to raise the fan cover plate, for passive cooling (supplied loose)
Note:	The door-opening angle may vary depending on site requirements or applications
Base material:	Carbon steel

Product features

© Rittal 2018

Dimensions:	Height: 2000 mm (79 ″) Width: 600 mm (24 ″) Depth: 1000 mm (39 ″)
Installation height for components:	42 U (42 U)
Distance between levels as delivered:	745 mm (29 ″)
482.6 mm (19") version:	Profile rails, 482.6 mm (19")
Construction doors:	Vented
Load capacity:	15000 N
Packaging unit:	1 pc(s).
Weight/packaging unit:	86.8 kg (191.4 lb.)
EAN:	4028177678200
Customs tariff number:	94032080
ETIM 6.0:	EC002499
ETIM 5.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 7.0/7.1:	27180207
eCl@ss 6.0/6.1:	27180207
eCl@ss 5.1/5.1.4:	27180201

Approvals

Approvals:	UL + C-UL