Rittal – The System.

Faster – better – everywhere.

Compact enclosures AE Stainless steel – AE 1006.500

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Compact enclosures AE Stainless steel – AE 1006.500

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Housing: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Carbon steel Stainless steel 1.4404 (AISI 316L) Lock Insert: Stainless steel 1.4404 (AISI 316L)
Surface finish:	Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
IK code:	IK08
Supply includes:	Housing with door(s) Mounting plate Lock: 3 mm double-bit
Product modification:	Starting in August 2016, the surface grinding is changing from 240 grain to 400 grain. The visually finer grinding pattern will enhance the cleaning properties of the housing.
Base material:	Stainless steel

Product features

Dimensions:	Height: 380 mm (15 ″) Width: 380 mm (15 ″) Depth: 210 mm (8.3 ″)

Mounting plate:	Height: 355 mm (14 ″) Width: 334 mm (13 ″)
Number of doors:	1
Lock version:	Cam
No. of locks:	1
Lock Insert:	3 mm double-bit
Packaging unit:	1 pc(s).
Weight/packaging unit:	9.8 kg (21.6 lb.)
EAN:	4028177421288
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	AE Compact enclosure, WHD: 380x380x210 mm, Stainless steel 1.4404, with mounting plate, single-door, with one cam lock

Approvals

Approvals:	Bureau Veritas CSA DNV-GL Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code Protection category
Declarations:	Declaration of conformity