Rittal – The System.

Faster – better – everywhere.

# Baying systems TS 8 Single – TS 8026.500

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# Baying systems TS 8 Single – TS 8026.500

created: 24.05.2018 build on www.rittal.com/us-en



## Product description

| | |
|---|---|
| **Material:** | Enclosure frame: Carbon steel, 1.5 mm<br>Roof: Carbon steel, 1.5 mm<br>Door: Carbon steel, 2.0 mm<br>Rear wall: carbon steel, 1.5 mm<br>Base plates: Carbon steel, 1.5 mm<br>Mounting plate: Carbon steel, 3.0 mm |
| **Surface finish:** | Enclosure frame: Dipcoat-primed<br>Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint<br>Mounting plate and base plates: Zinc-plated |
| **Color:** | RAL 7035 |
| **Protection category IP to IEC 60 529:** | IP 55 |
| **Protection category NEMA:** | NEMA 12 |
| **Supply includes:** | Enclosure frame with door<br>Roof plate<br>Rear panel, detachable<br>4 eyebolts<br>Lock: 3 mm double-bit<br>Base Plates<br>Mounting plate |

## Product features

| | |
|---|---|
| **Dimensions:** | Height: 2200 mm (87 ″)<br>Width: 1000 mm (39 ″)<br>Depth: 600 mm (24 ″) |

| | |
|---|---|
| **Number of doors:** | 1 |
| **Packaging unit:** | 1 pc(s). |
| **Weight/packaging unit:** | 140.5 kg (309.7 lb.) |
| **EAN:** | 37965 |

## Approvals

| | |
|---|---|
| **Approvals:** | Bureau Veritas<br>CSA<br>DNV-GL<br>Russian Maritime Register of Shipping<br>TÜV UL + C-UL |