Rittal – The System.

Faster – better – everywhere.

TopTherm Blue e roof-mounted cooling units Total cooling output 0.50 - 4.00 kW – SK 3386.640

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TopTherm Blue e roof-mounted cooling units Total cooling output 0.50 - 4.00 kW – SK 3386.640

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Stainless steel
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit, IP 54
Supply includes:	Nano-coated condenser Integral electric condensate evaporation Wired ready for connection (plug-in terminal strip) Drilling template Fasteners
Note:	Due to its low noise level, the roof-mounted cooling unit 3273.500 is also suitable for use in office applications.
Note on Model No.::	Delivery times on request.

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 3 kW (10236 BTU) L 35 L 35 at 60 Hz: 3.3 kW (11260 BTU) L 35 L 50 at 50 Hz: 2.2 kW (7506 BTU) L 35 L 50 at 60 Hz: 2.5 kW (8530 BTU)
Air throughput (unimpeded air flow):	External circuit: 3450 m³/h (2030.6 cfm) Internal circuit: 1280 m³/h (753.4 cfm)
Rated operating voltage:	400 V, 3~, 50 Hz 460 V, 3~, 60 Hz

© Rittal 2018

Dimensions:	Height: 470 mm (19 ″) Width: 796 mm (31 ″) Depth: 580 mm (23 ″)
Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 1600 g (56.4 oz) Global Warming Potential (GWP): 1430 CO_2 equivalent (CO_2e): 2.29 t
Type of connection (electrical):	Plug-in terminal strip
Duty cycle:	100 %
Rated power Pel:	L 35 L 35 at 50 Hz: 1.17 kW L 35 L 35 at 60 Hz: 1.48 kW L 35 L 50 at 50 Hz: 1.42 kW L 35 L 50 at 60 Hz: 1.76 kW
Rated current (max.):	At 50 Hz: 3.4 A At 60 Hz: 3.4 A
Start-up current (max.):	At 50 Hz: 8 A At 60 Hz: 9 A
Pre-fuse:	Motor circuit-breaker: 6,3 A...10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.56
Packaging unit:	1 pc(s).
Weight/packaging unit:	70 kg
EAN:	4028177380226
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704

© Rittal 2018

eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description (long):	SK cooling unit Blue e, roof-mounted, 3 kW, 400-460 V, 3~, 50/60 Hz, Stainless steel, WHD: 796 x 470 x 580 mm

Approvals

Approvals:	CSA TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation

© Rittal 2018