Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure Stainless steel – WM 9851.503

Date : Jun 1, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure Stainless steel – WM 9851.503 - WM242412N43PT

created: 01.06.2018 build on www.rittal.com/us-en



Product description

Material:	Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated
Surface finish:	Brushed
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Wall mounting blind-nuts

Product features

Dimensions:	Height: 600 mm (24 ″) Width: 600 mm (24 ″) Depth: 300 mm (12 ″)
Material thickness::	Housing: 1.5 mm (0.06 ″) Door: 2 mm (0.08 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 549 mm (22 ″) Width: 570 mm (22 ″)

Lock version:	3-point locking system
Packaging unit:	1 pc(s).
Weight/packaging unit:	28 kg (61.7 lb.)
EAN:	87294

Approvals

Approvals:	UL + C-UL