Rittal – The System.

Faster – better – everywhere.

# Wallmounted enclosure Stainless steel – WM 8018.500

Date : May 26, 2017

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# Wallmounted enclosure Stainless steel – WM 8018.500 - WM363016N4

created: 26.05.2017 build on www.rittal.com/us-en



## Product description

| | |
|---|---|
| **Material:** | Door: Stainless steel, all-round foamed-in PU seal<br>Housing and door: Stainless steel 1.4301 (AISI 304)<br>Mounting plate: Carbon steel, zinc-plated |
| **Surface finish:** | Brushed |
| **Protection category IP to IEC 60 529:** | IP 66 |
| **Protection category NEMA:** | NEMA 4X |
| **Supply includes:** | Housing with door(s)<br>Left hand hinge<br>Mounting plate<br>Wall mounting blind-nuts |

## Product features

| | |
|---|---|
| **Dimensions:** | Height: 900 mm (35 ″)<br>Width: 760 mm (30 ″)<br>Depth: 400 mm (16 ″) |
| **Material thickness::** | Housing: 2 mm (0.08 ″)<br>Door: 2 mm (0.08 ″)<br>Mounting plate: 2.5 mm (0.1 ″) |
| **Mounting plate:** | Height: 870 mm (34 ″)<br>Width: 704 mm (28 ″) |

Â© Rittal 2017

| | |
|---|---|
| **Lock version:** | Quarter turn |
| **Packaging unit:** | 1 pc(s). |
| **Weight/packaging unit:** | 61 kg (134.5 lb.) |

## Approvals

| | |
|---|---|
| **Approvals:** | UL + C-UL |

2017 © Rittal Corporation