Rittal – The System.

Faster – better – everywhere.

Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.600

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Stainless steel
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit, IP 54
Supply includes:	Nano-coated condenser Wired ready for connection (plug-in terminal strip) Drilling template Fasteners
Note:	The technical specifications for the wall-mounted cooling unit 3361.540 are valid with an external transformer connected.
Note on Model No.::	Delivery times on request.

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 0.85 kW (2900 BTU) L 35 L 35 at 60 Hz: 0.89 kW (3036 BTU) L 35 L 50 at 50 Hz: 0.67 kW (2286 BTU) L 35 L 50 at 60 Hz: 0.67 kW (2286 BTU)
Air throughput (unimpeded air flow):	External circuit: 550 m³/h (323.7 cfm) Internal circuit: 230 m³/h (135.4 cfm)
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 550 mm (22 ″)

Â© Rittal 2018

	Width: 280 mm (11 ″) Depth: 280 mm (11 ″)
Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Operating temperature (max.) 60 Hz: +53°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 280 g (9.9 oz) Global Warming Potential (GWP): 1430 CO_2 equivalent (CO_2e): 0.4 t
Rated power Pel:	L 35 L 35 at 50 Hz: 0.4 kW L 35 L 35 at 60 Hz: 0.43 kW L 35 L 50 at 50 Hz: 0.47 kW L 35 L 50 at 60 Hz: 0.5 kW
Rated current (max.):	At 50 Hz: 2.7 A At 60 Hz: 2.7 A
Start-up current (max.):	At 50 Hz: 6 A At 60 Hz: 9.6 A
Miniature circuit-breaker/fuse:	10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.08
Packaging unit:	1 pc(s).
Weight/packaging unit:	22 kg (48.5 lb.)
EAN:	4028177429574
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704

Product description (long):	SK cooling unit Blue e, wall-mounted, 0.85 kW, 230 V, 1~, 50/60 Hz, Stainless steel, WHD: 280 x 550 x 280 mm

Approvals

Approvals:	CSA TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation