Rittal – The System.

Faster – better – everywhere.

Courtesy light – SZ 4139.150

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Courtesy light – SZ 4139.150

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	with door-operated switch
Supply includes:	Courtesy light Light (bulb) Light cover Assembly components Integral door-operated switch

Product features

Dimensions:	Height: 117 mm (4.6 ″) Width: 452 mm (18 ″) Depth: 50 mm (2 ″)
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz
Installation options:	TS horizontal profile from roof frames: direct TS, SE vertical section: with TS adapter bracket SE sections on front and rear of roof frame: with TS adapter bracket SE profiles to the side of roof frames: direct
Operating temperature:	Operation (environment): -15°C...+45°C Storage: -20°C...+70°C
Power consumption:	14 W
Equipment (electrical):	Ballast: Wide range voltage EB Light (bulb): Fluorescent lamp, G13 backplate Jack/outlet (type): D, ground contact (type F, CEE 7/4) Integral door-operated switch: yes Switch (type): Integral, on/off/door-operated switch mode

© Rittal 2018

Rated insulation voltage:	500 V DC/1s
Rated impulse withstand voltage, phase to earth:	1000 V AC
Rated impulse withstand voltage, phase to phase:	500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply through connector Through-wiring (configuration of row of luminaires)
Light – installation type:	Screw fastening
Light cover:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	2.02 kg (4.5 lb.)
EAN:	4028177320741
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Courtesy light, WHD: 452x117x50 mm, 14 W, 100-240 V, 50/60 Hz, with door-operated switch, with earthing-pin socket

Approvals

Certificates:	EAC
Declarations:	Declaration of conformity