# Product data sheet
## Characteristics

# VJDSNDTGSV62M
## Vijeo Designer 6.2, HMI configuration software single license




### Main

| | |
|---|---|
| Range of product | Vijeo Designer |
| Product or component type | Configuration software |
| Language | French<br>English<br>German<br>Italian<br>Chinese<br>Spanish<br>Portuguese |
| Format | DVD-ROM |
| Previous software version | V6.1 |
| Type of license | Single (1 station) |
| Software version | V6.2 |

### Complementary

| | |
|---|---|
| Range compatibility | Harmony XBT GH<br>Harmony XBT GTW<br>Harmony Compact iPC<br>Harmony XBT GK<br>Harmony GTO<br>Harmony STO & STU<br>Harmony XBT GT<br>Harmony Smart<br>Harmony GTU<br>Harmony iPC |
| Software designation | Vijeo Designer |
| System requirements | Processor suitable for operating system Windows 7 Professional 32/64 bit<br>Processor suitable for operating system Windows 8.1<br>Processor suitable for operating system Windows 10 Professional 32/64 bit |
| Product compatibility | SoMachine V4.1 or higher |
| Communication port protocol | MELSEC<br>Modbus RTU master<br>Modbus TCP master<br>Sysmacway<br>Ethernet/IP Explicit<br>Modbus 32-bit extensions<br>Profibus DP<br>ELAU PacDrive<br>ROC Plus<br>Allen-Bradley<br>UniTE TCP/IP<br>USB<br>Simatic<br>Toyopuc PC3J<br>Uni-Telway<br>Modbus Plus<br>Fipio/Fipway |
| Provided equipment | Acrobat Reader<br>Tutorial in flash format<br>User's documentation in electronic format<br>Vijeo Designer software |
| Software function | 8000 variables<br>9999 alarms<br>4 asian alphabets<br>2 middle eastern alphabets<br>Sharing up to 300 variables<br>34 western alphabets |
| Audio video coding standard | JPEG |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

| | |
|---|---|
| Category | 22569 - MAGELIS XBT-GT (AND XBT-G) |
| Discount Schedule | MC2 |
| GTIN | 00785901714446 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.23 lb(US) (0.10 kg) |
| Returnability | Yes |
| Country of origin | FR |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.55 in (1.4 cm) |
| Package 1 width | 5.51 in (14 cm) |
| Package 1 Length | 6.50 in (16.5 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 16 |
| Package 2 Weight | 4.37 lb(US) (1.98 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

## Offer Sustainability

| | |
|---|---|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |