# Product data sheet
## Characteristics

# TVS4IMA24O
## OEM assembler kit, Surgelogic, 240kA, 480Y/277VAC, 3 phase, 4 wire, SPD type 2



## Main

| | |
|---|---|
| Product | Surge protection device |
| Range | Surgelogic |
| Device Short Name | IMA |

## Complementary

| | |
|---|---|
| Voltage Rating | 277Y/480 V AC |
| MCOV | 320 V |
| SCCR | 200 kA |
| Surge Current | 240 kA per phase |
| Nominal Discharge Current | 20 kA |
| Number of Phases | 3 phase |
| Wiring Configuration | 4-wire |
| Connection | Lugs AWG 12...AWG 2 aluminium/copper 35.4 lbf.in (4 N.m) |
| Provided Equipment | Alarm enable/disable switch<br>Diagnostic display<br>Backplane<br>Cables |
| Height | 6.1 in (155.7 mm) |
| Width | 9.9 in (250.4 mm) |
| Depth | 3.6 in (92.7 mm) |

## Environment

| | |
|---|---|
| Enclosure Rating | NEMA 2 |
| Standards | UL 1449:ed. 4<br>CSA C22.2 No 8:1986<br>UL 96A:ed. 12<br>UL 1283<br>IEC 61643-1 |

## Ordering and shipping details

| | |
|---|---|
| Category | US1DE1B08468 |
| Discount Schedule | DE1B |
| GTIN | 785901600831 |
| Returnability | Yes |
| Country of origin | US |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.0000000000 in (17.78 cm) |
| Package 1 Width | 9.0000000000 in (22.86 cm) |
| Package 1 Length | 12.0000000000 in (30.48 cm) |
| Package 1 Weight | 8.600 lb(US) (3.901 kg) |

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |