Product data sheet
Characteristics

5NR401
TRANSFORMER CURRENT 400:5 1-9/16 ID



Main

Product	General Purpose Current Transformer
Certifications	UL Recognized
Ratio	400/5
Enclosure Type	NEMA 1
Phase	1 phase
Power Rating	12.5 VA
Eletrical Connection	Flying leads 24 in (609.60 mm), AWG 16
Opening Size	Ø 1.56 in

Ordering and shipping details

Category	15500 - CLASS 4210 CT'S (LC 5101)
Discount Schedule	PA1
GTIN	00785901099307
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	1.50 in (3.810 cm)
Package 1 width	4.20 in (10.668 cm)
Package 1 Length	4.20 in (10.668 cm)

Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.