Product data sheet
Characteristics

2510KS2B
Manual Switch - SS Flush - 3P - Toggle Operated - Red Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 223.20 USD

Main

Product or component type	Single Unit Manual Switch
Range of product	K

Complementary

Line Rated Current	30 A
Motor power hp	2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC
System Voltage	600 V AC 230 V DC
Poles description	3P
Control type	Toggle
Phase	3 phases
Local signalling	Red indicator 208...277 V
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 10 (copper)
Height	4.5 in
Width	2.75 in
Depth	2.5 in

Environment

Product certifications	CE UL listed file E42243 CCN NLRV

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	CSA LR25490 class 3211 05
NEMA degree of protection	Not rated (flush plate) stainless steel standard size

Ordering and shipping details

Category	21102 - 2510,2511,2512 K
Discount Schedule	CP1
GTIN	00785901006039
Nbr. of units in pkg.	1
Package weight(Lbs)	0.54000000000000004
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months