Product data sheet
Characteristics

2510KG6B
Manual Switch - NEMA 1 - 3P - Toggle Operated - Red Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 240.00 USD



Main

Product or component type	Single Unit Manual Switch
Range of product	K
Line Rated Current	30 A
Product certifications	CSA CE UL listed
Cable entry	0.5" and 0.75" knock-outs (top and bottom)
NEMA degree of protection	NEMA 1 painted sheet steel standard size
Motor power hp	1 hp 90 V DC 15 hp 460 V AC 2 hp 115 V AC 2 hp 115 V DC 20 hp 575 V AC 1.5 hp 230 V DC 7.5 hp 230 V AC
System Voltage	600 V AC 230 V DC
Poles description	3P
Control type	Toggle
Phase	3 phases
Local signalling	Red indicator 208...277 V
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals

Ordering and shipping details

Category	21102 - 2510,2511,2512 K
Discount Schedule	CP1
GTIN	00785901005957

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package weight(Lbs)	0.80000000000000004
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months