Product data sheet
Characteristics

9998LX55
Replacement unlatch coil, 277VAC 60Hz, 8903L Contactor, 2-12 poles



Main

Product or component type	Coil
Accessory / separate part destination	Class 8903 contactor

Complementary

[Ue] rated operational voltage	277 V AC 60 Hz
Inrush power in VA	180 VA
Maximum Height	1.75 in (44.5 mm)
Maximum Width	2.46 in (62.5 mm)
Maximum Depth	1.13 in (28.7 mm)

Ordering and shipping details

Category	21756 - 9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	00785901057703
Nbr. of units in pkg.	1
Package weight(Lbs)	0.22 lb(US) (0.10 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	1.30 in (3.302 cm)
Package 1 width	2.30 in (5.842 cm)
Package 1 Length	3.10 in (7.874 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.