Product data sheet

Specifications



Unit Substation, Mini Power-Zone, 1 Phase, 25kVA, 480V Pri, 120/240V Sec, Type 3R, 304SS, 18kA, wall mounted, bolt on

MPUB25S40FSS

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Certifications	UL Listed
Type	Mini Power-Zone
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	25 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Interior Type	NQ Panelboard interior
Number of Spaces Available	28.0
Number of Circuits	28.0
Enclosure Type	NEMA 3R stainless steel 316

Complementary

Height	27.40 in (695.96 mm)
Width	51.0 in (1295.4 mm)
Depth	13.5 in (342.9 mm)
Product Weight	441.92 lb(US) (200.45 kg)

Ordering and shipping details

Category	US10PE216276
Discount Schedule	0PE2
GTIN	3606487189435
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	13.5 in (34.3 cm)
Package 1 Width	27.4 in (69.6 cm)
Package 1 Length	51.02 in (129.6 cm)
Package weight(Lbs)	544.8 lb(US) (247.1 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Take-back	**No**