# Product data sheet

Specifications



## TYPE 1 200A 240V MOULDED CASE CIRCUIT BREAKER ENCLOSURE

Q22200NS

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product Type** | Enclosure |
| **Range of Product** | PowerPact Q |

## Complementary

| | |
|---|---|
| **Rated Current** | 200 A |
| **Number of Poles** | 2P |
| **Enclosure Rating** | NEMA 1 indoor |
| **Breaker Compatibility** | Circuit breaker PowerPacT |
| **Product Certifications** | CSA<br>UL |
| **Voltage Rating** | 240 V AC |
| **Tightening Torque** | 28 N.m, AWG 4...300 kcmil |
| **Enclosure Material** | Steel |
| **Height** | 23.1 in (588 mm) |
| **Width** | 7.6 in (194 mm) |
| **Depth** | 4.3 in (108 mm) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1DE2A00005 |
| **Discount Schedule** | DE2A |
| **GTIN** | 785901785446 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 5.500 in (13.970 cm) |
| **Package 1 Width** | 9.100 in (23.114 cm) |
| **Package 1 Length** | 25.300 in (64.262 cm) |
| **Package weight(Lbs)** | 11.766 lb(US) (5.337 kg) |
| **Unit Type of Package 2** | PAL |
| **Number of Units in Package 2** | 56 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 2 Height** | 40.000 in (101.600 cm) |
| **Package 2 Width** | 40.000 in (101.600 cm) |
| **Package 2 Length** | 48.000 in (121.920 cm) |
| **Package 2 Weight** | 660.999 lb(US) (299.824 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **41 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **32 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **2 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **8 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| SCIP Number | **7123f656-319e-4ae7-888d-d29a63a4aa90** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |
| Halogen content performance | **Halogen free plastic parts product** |
| PVC free | **Yes** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **95** |
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |

| | |
|---|---|
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |