# Product data sheet
## Characteristics

# MPU15S40F
## Unit substation, Mini Power-Zone, plug on, 15kVA, 1 phase, 480V primary, 120/240V secondary, 18kA, B



### Main

| | |
|---|---|
| Product | Sealed Transformer |
| Certifications | UL Listed |
| Type | Mini Power-Zone |
| Enclosure Code | B |
| Insulation Temperature | 365.0000000000 °F (185 °C) |
| Phase | 1 phase |
| Primary Voltage | 480 V |
| Secondary Voltage | 120/240 V |
| Full Capacity Taps | 2 5 % FCBN |
| Power Rating | 15 kVA |
| Temperature Rise | 115 °C |
| Winding Material | Copper |
| Interrupt Rating | 18 kA |
| Circuit Breaker Type | Primary main breaker<br>Secondary main breaker<br>Feeder breaker |
| Interior Type | QO Load Center interior |
| Number of Spaces Available | 22 |
| Number of Circuits | 10 |
| Enclosure Type | NEMA 3R hot-rolled steel |

### Complementary

| | |
|---|---|
| Height | 43.20 in (1097.28 mm) |
| Width | 21.00 in (533.40 mm) |
| Depth | 13.50 in (342.90 mm) |
| Product Weight | 350.006 lb(US) (158.76 kg) |

### Ordering and shipping details

| | |
|---|---|
| Category | US10PE216275 |
| Discount Schedule | 0PE2 |
| GTIN | 785901699187 |
| Returnability | No |
| Country of origin | US |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 43.2 in (109.7 cm) |
| Package 1 Width | 21.0 in (53.3 cm) |
| Package 1 Length | 13.5 in (34.3 cm) |
| Package 1 Weight | 365.000 lb(US) (165.561 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Under investigation |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |