
Product data sheet

Specifications



Contactor, Definite Purpose, auxiliary contact, 3A at 120 VAC, 2 NO contacts, for 20A to 90A DPA contactors

9999D20

Product availability: Stock - Normally stocked in distribution facility

Main

Product Range	DPA
Component type	Auxiliary Contact Module
Used with	contactor

Complementary

Auxiliary contact composition	2 NO
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.75 A 480 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A <= 600 V AC resistive control circuit UL 508

Environment

Product Certifications	CSA UL Recognized

Ordering and shipping details

Category	US1CP1B21762
Discount Schedule	CP1B
GTIN	785901081319
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.700 in (1.778 cm)
Package 1 Width	1.800 in (4.572 cm)
Package 1 Length	3.700 in (9.398 cm)
Package weight(Lbs)	1.440 oz (40.823 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	4.600 in (11.684 cm)
Package 2 Width	4.600 in (11.684 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	10.400 in (26.416 cm)
Package 2 Weight	2.661 lb(US) (1.207 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**