Product data sheet

Specifications



Overload Relay, Motor Logic, solid state, isolated alarm contacts

9999AC04

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Accessory
Product destination	Overload relay
Thermal overload type	Solid state

Complementary

Product or Component Type	Auxiliary contact
Contacts type and composition	1 NO
[Ue] rated operational voltage	600 V AC

Ordering and shipping details

Category	US10CP121761
Discount Schedule	0CP1
GTIN	785901070719
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.300 in (3.302 cm)
Package 1 Width	2.300 in (5.842 cm)
Package 1 Length	3.100 in (7.874 cm)
Package weight(Lbs)	0.800 oz (22.680 g)

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.